

Product Information ISO Class 5 – 8 Cleanroom Class 100 – 100,000 EU Grade B/C/D

SatPax® 1000 Pouch

Pre-wetted 55% Cellulose / 45% Polyester Nonwoven Cleanroom Wiper

SatPax[®] 1000 combines Durx[®] 670 nonwoven wipers composed of a hydroentangled nonwoven blend of 55% cellulose and 45% polyester with various saturation levels of isopropyl alcohol and DI water. This pre-wetted format provides a cost-effective and easy-to-use solution versus traditional bulk handling of solvents, maintenance of squirt bottles and inconsistent wetting and cleaning associated with wetting a dry wiper



Other Class 5 and above Pre-wetted wipers

- SatPax[®] 670
- SatPax[®] 550

Key Attributes

- 55% cellulose / 45% polyester hydroentangled nonwoven blend
- No chemical binders in base material
- Pre-wetted with consistent IPA / DI Water concentrations and saturation levels
- Re-sealable solvent resistant packaging with wipers in a c-folded configuration for single withdrawal
- Also available in canister dispensers—wipers in perforated roll configuration for pop-up convenience

Benefits

- Low extractables and fiber and particle counts
- Smooth and durable with good wet strength
- Reduces alcohol usage and preparation / handling costs
- Reduces VOC emissions
- Increases cleaning efficiency
- Increases cleaning protocol consistency

Environmental

Registered under REACH

Applications

- Designed for use in ISO Class 5 and higher cleanroom environments
- Designed for use in wet cleaning of critical surfaces where control of flammable solvents and flammable solvent
 concentrations is required
- Final cleaning of surfaces or products prior to manufacturing or packaging
- · High saturation level is ideal for removing cleaning and disinfecting residues in regulated environments

Alcohol Mixtures

Alcohol / DI Water mixtures can be varied to fit the customer requirements. Typical mixtures are 70/30 and 9/91 IPA/DI Water.

Saturation Levels

The amount of solution contained in each wiper can be varied according to customer requirements. Higher saturation levels apply more solution to the surface during cleaning.

Sterile Validated Option

For aseptic processing areas, the same wiper material can be provided in a gamma irradiated validated sterile to a 10⁻⁶ sterility assurance level.

www.berkshire.uk.com

Contact: Tel + 44 1953 562800 enquiries@berkshire.uk.com

America	Tel 1 413 528 2602	info@berkshire.com
Europe		
SE Asia	Tel 65 6252 4313	enquiries@berkshire.com.sg
Japan	Tel 81 3 4530 9883	master@berkshire.co.jp



Technical Data (In Dry State)

Attribute		Units	Value	Test Method	
Basis Weight		g/m ²	68.0	TAPPI T-410	
Caliper		μm	264	TAPPI T-411	
Fibres	≥100µm	fibres/cm ²	160	IEST-RP-CC004.4 Sec 7.1.3/Sec 7.2.2 modified	
Particles	≥0.5µm	x10 ³ /cm ²	10	IEST-RP-CC004.4 Sec 7.1.3/Sec 7.2.1 modified	
Sorbency	Capacity	mL/m²	320	IEST-RP-CC004.4 Sec 9.1 / Sec 9.2 modified	
	Efficiency	mL/g	4.7		
	Rate	seconds	2		
Non-Volatile Residue	DI Water	g/m²	0.028	IEST-RP-CC004.4 Sec 8.1.2	
	IPA	g/m ²	0.0038		
Ions	Na⁺	ppm	62	IEST-RP-CC004.4 Sec 8.2.2	
	K+	ppm	5.9		
	Ca++	ppm	22		
	Mg ⁺⁺	ppm	5.0		
	CI	ppm	31		

Notes:

- Technical data represented in this table are typical values at the time of publication. These should not be used as
 product specifications.
- Due to differences in test methods applied and equipment utilised by different wiper manufacturers, valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions
- Third party testing can be performed upon request

Order Information:

Product	Number	Size	Shts/pk	Pks/cs	IPA/DI	Saturation	VOC % by Weight	Style
SatPax® 1000	SPX1000.001.12	9x9" (23x23cm)	75	12	70/30	45%	35%	Pouch
SatPax® 1000	SPX1000.002.12	9x9" (23x23cm)	75	12	09/91	45%	4.7%	Pouch
SatPax® 1000	SPX1000.011.12	9x9" (23x23cm)	75	12	6/94	45%	3.1%	Pouch
SatPax® 1000	SPX100001212	6x9" (15x23cm)	100	12	70/30	75%	48%	Zipper Pouch



www.berkshire.uk.com

Contact: Tel + 44 1953 562800 / info@berkshire.uk.com BIL 1200 09-2023